


姿図



品番	DL-RD09WS
光源	LED 4000K 30W
定格光束	1481 lm
1/2照度角	62°
ビーム角	96°

器具効率	100.0 %
上方光束	0.5 %
下方光束	99.5 %
器具間隔 最大限 (取付高さH)	A 1.21 H
	B 1.21 H
保守率	良 0.63
	中 0.60
	否 0.53

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 (× 0.01)													
0.6	51	43	38	50	43	38	49	42	38	48	42	37	35	
0.8	61	53	47	60	53	47	59	52	47	57	51	46	44	
1	70	62	56	68	61	55	66	60	55	64	59	54	52	
1.25	77	70	64	76	69	63	73	67	62	71	66	62	59	
1.5	83	76	70	81	75	69	79	73	68	76	71	67	64	
2	91	85	79	89	83	79	86	81	77	83	79	76	72	
2.5	96	90	86	94	89	85	91	86	83	88	84	81	77	
3	100	95	91	98	93	89	94	90	87	91	88	85	81	
4	100	100	96	100	98	95	98	95	92	94	92	89	85	
5	100	100	100	100	100	98	100	98	95	96	94	92	88	

