


姿図



品番	DL-DD15L
光源	LED 50W(3000K)
定格光束	3050.0 lm
1/2照度角	17°
ビーム角	18°

器具効率	100.0 %
上方光束	0.0 %
下方光束	100.0 %
器具間隔 最大限 (取付高さH)	A 0.29 H
	B 0.29 H
保守率	良 0.63
	中 0.60
	否 0.53

反射率 (%)	天井	80			70			50			30			0
	壁	50	30	10	50	30	10	50	30	10	50	30	10	0
	床	20			20			20			20			0
室指数	照 明 率 ( × 0.01 )													
0.6	78	73	70	78	73	70	77	73	70	76	72	70	68	
0.8	85	80	76	84	79	76	83	78	75	81	78	75	73	
1	90	85	82	89	85	81	88	84	81	86	83	80	78	
1.25	95	90	87	94	90	86	92	88	85	90	87	84	82	
1.5	99	94	91	97	93	90	95	92	89	93	90	88	85	
2	104	100	97	102	99	96	100	97	95	97	95	93	90	
2.5	107	104	102	106	103	101	103	101	99	100	98	97	93	
3	110	108	105	108	106	104	105	103	102	102	100	99	95	
4	113	111	109	111	109	108	107	106	105	104	103	102	98	
5	114	113	111	112	111	110	108	107	106	105	104	103	99	

